

# Technical Bulletin

## 607 – Remote Control to Broadcast Tools TeleSwitch Six

### Hybrid Connections

**Brand/Model**  
**DI-2000**

**Connections:**

DB-25 connector for Line 1 Pin 14 (Air Switch) to  
TS-6 Controller J7 pin 4.

DB-25 connector for Line 1 Pin 21 (Ground) to  
TS-6 Controller J7 pin 5.

DB-25 connector for Line 1 Pin 1 (Drop Switch) to  
TS-6 Controller J7 pin 6.

DB-25 connector for Line 1 Pin 22 (Ground) to  
TS-6 Controller J7 pin 7.

DB-25 connector for Line 2 Pin 14 (Air Switch) to  
TS-6 Controller J7 pin 8.

DB-25 connector for Line 2 Pin 21 (Ground) to  
TS-6 Controller J7 pin 9.

DB-25 connector for Line 2 Pin 1 (Drop Switch) to  
TS-6 Controller J7 pin 10.

DB-25 connector for Line 2 Pin 22 (Ground) to  
TS-6 Controller J7 pin 11

**Note: Set TS-6 Controller DIP 2 to select dual  
hybrid mode, and set TS-6 Controller DIP 7&8 for  
pulse mode.**



601 Heron Drive  
Logan Township, NJ 08085  
Phone: 856-467-8000 • Fax: 856-467-3044  
<http://www.radiosystems.com>